

# CAMERA SPECIFICATIONS

|                                      |  |
|--------------------------------------|--|
| <b>Vendor Model #/Style #</b>        | 63074  |
| <b>Camera Model</b>                  | Primos Truth Cam 40 Ultra -- 7MP Game Camera                               |
| <b>Shooting modes</b>                | Photos, Videos, All-Day Time Lapse, Time Lapse with PIR Day & Night Photos |
| <b>Image sensor</b>                  | 5.0 MP Color CMOS  |
| <b>Photo resolution settings</b>     | Large(3072x2304), Small(2592x1944)   |
| <b>Photo burst settings</b>          | 1, 2, 3, 4, 5  |
| <b>Video resolution settings</b>     | 640x480(30fps), 320x240(30fps)   |
| <b>Video length settings</b>         | 5s, 10s, 15s, 20s, 30s, 60s  |
| <b>Sound Recording</b>               | n/a  |
| <b>Time Lapse Video Resolution</b>   | 1280x960 (10fps)   |
| <b>Time Lapse interval settings</b>  | 10s, 20s, 30s, 1m, 5m, 30m   |
| <b>Lens</b>                          | 7.5mm f/3.0  |
| <b>Field of View</b>                 | 55°  |
| <b>Zoom</b>                          | fixed  |
| <b>ISO sensitivity</b>               | 100  |
| <b>Infrared Illumination</b>         | 40 High-Output IR Emitters;Up to 45ft                                      |
| <b>PIR Sensor</b>                    | Multi Zone   |
| <b>PIR Sensitivity</b>               | Auto   |
| <b>Trigger Time</b>                  | 1 Second   |
| <b>Removable Memory</b>              | up to 32 GB SD Card  |
| <b>System requirements (Windows)</b> | Windows 2000, XP, Vista or Win7; USB port                                  |
| <b>System requirements (Mac)</b>     | Mac OS X 10.3 or later; USB port   |

|   |  |
|---|--|
| <b>Display</b>                          | 1.1" Character LCD   |
| <b>User Interface</b>                   | Sliding Switches   |
| <b>Image Stamp</b>                      | Burst Count, Moon Phase, Temperature, 12 Hour US Time (AM/PM), Date, Day of the Week |
| <b>Memory</b>                           | SD Memory up to 32 GB card size (not included)                                       |
| <b>Mounting</b>                         | Adjustable Webbing Strap with Buckle   |
| <b>Power requirements</b>               | 8xAA Batteries (not included); 6-12V DC in   |
| <b>Standby Current</b>                  | < 0.25 mA (<mAh/Day)   |
| <b>Power Consumption (12v Power in)</b> | 90mA (+960mA with IR)  |
| <b>Power Consumption</b>                | *SD Card Slot<br>USB Jack<br>6V-12V DC Jack*   |
| <b>Product height (in.)</b>             | 2.5  |
| <b>Product width (in.)</b>              | 4.25   |
| <b>Product length (in.)</b>             | 5.25   |
| <b>Product weight (lb)</b>              | Approx 1.5lbs  |
| <b>Operation / Storage Temps</b>        | *Storage: -10°F to 140°F<br>Operation: 20°F to 120°F*                                |
| <b>Security Authentication</b>          | FCC, CE  |