

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

Product Identifier

Product Form: Mixture

Product Name: RCBS Press Storage Aerosol

Intended Use of the Product : Firearm Lubricant and Rust Preventative

Name, Address, and Telephone of the Responsible Party

Company

Federal Cartridge Company

900 Ehlen Drive
Anoka, MN 55303

T 1-800-635-7656

Emergency Telephone Number

Emergency number : 1-800-424-9300 (Inside US), 01-703-527-3887 (Outside US) - (CHEMTREC, Day or Night)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Simple Asphy

Flam. Aerosol 1 H222

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

STOT SE 3 H336

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H222 - Extremely flammable aerosol
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
May displace oxygen and cause rapid suffocation

Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Pressurized container: Do not pierce or burn, even after use.
P260 - Do not breathe gas, vapors, mist, spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, respiratory protection.
P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTER/doctor/physician if you feel unwell.
P314 - Get medical advice and attention if you feel unwell.
P321 - Specific treatment (see section 4).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362 - Take off contaminated clothing and wash before reuse.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F
P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Flammable vapors can accumulate in head space of closed systems.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	71	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Calcium petroleum sulfonate	(CAS No) 61789-86-4	12	Eye Irrit. 2A, H319 Skin Sens. 1B, H317 Aquatic Acute 2, H401
Distillates, petroleum, hydrotreated heavy paraffinic	(CAS No) 64742-54-7	12	Not classified
Propane	(CAS No) 74-98-6	12.5	Simple Asphy Flam. Gas 1, H220 Liquefied gas, H280
Butane	(CAS No) 106-97-8	12.5	Simple Asphy Flam. Gas 1, H220 Liquefied gas, H280
Diethylene Glycol Monobutyl Ether	(CAS No) 112-34-5	1	Eye Irrit. 2A, H319
Distillates, petroleum, hydrotreated light naphthenic	(CAS No) 64742-53-6	4	Asp. Tox. 1, H304

More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary due to varying composition.

Full text of H-phrases: see section 16

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Get immediate medical advice/attention.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Ingestion: Rinse mouth. Do NOT induce vomiting. Seek medical attention immediately.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes damage to organs. Causes eye irritation. Causes skin irritation. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness and dizziness. Asphyxiant gas.

Inhalation: Respiratory tract irritation. May cause drowsiness or dizziness. Asphyxia by lack of oxygen: risk of death.

Skin Contact: May cause skin irritation. May cause an allergic skin reaction.

Eye Contact: May cause eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects. May be fatal if swallowed and enters airways.

Chronic Symptoms: None

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Extremely flammable aerosol.

Explosion Hazard: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Toxic fumes are released.

Other information: Do not allow run-off from fire fighting to enter drains or water courses. Do not allow the product to be released into the environment.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do NOT breathe (vapor, mist, spray, gas). Do not get in eyes, on skin, or on clothing.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Use only non-sparking tools. Contact competent authorities after a spill. Isolate area until gas has dispersed.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use. Flammable vapours can accumulate in head space of closed systems. When heated to decomposition, emits toxic fumes.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do not eat, drink or smoke when using this product. Wash hands, forearms, and other exposed areas thoroughly after handling.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Prevent build-up of electrostatic charges (e.g., by grounding). Comply with applicable regulations. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from extremely high or low temperatures, direct sunlight, ignition sources, incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Storage Temperature: < 48 °C (120°F)

Storage Area: Store locked up.

Special Rules on Packaging: Keep only in the original container.

Specific End Use(s) Not available

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Propane (74-98-6)		
USA ACGIH	ACGIH TWA (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL TWA (ppm)	1000 ppm
Manitoba	OEL TWA (ppm)	1000 ppm
Newfoundland & Labrador	OEL TWA (ppm)	1000 ppm
Nova Scotia	OEL TWA (ppm)	1000 ppm
Ontario	OEL TWA (ppm)	1000 ppm
Prince Edward Island	OEL TWA (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1800 mg/m ³
Québec	VEMP (ppm)	1000 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Butane (106-97-8)		
Mexico	OEL TWA (mg/m ³)	1900 mg/m ³
Mexico	OEL TWA (ppm)	800 ppm
USA ACGIH	ACGIH STEL (ppm)	1000 ppm

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA NIOSH	NIOSH REL (TWA) (mg/m ³)	1900 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	800 ppm
Alberta	OEL TWA (ppm)	1000 ppm
British Columbia	OEL STEL (ppm)	750 ppm
British Columbia	OEL TWA (ppm)	600 ppm
Manitoba	OEL STEL (ppm)	1000 ppm
New Brunswick	OEL TWA (mg/m ³)	1900 mg/m ³
New Brunswick	OEL TWA (ppm)	800 ppm
Newfoundland & Labrador	OEL STEL (ppm)	1000 ppm
Nova Scotia	OEL STEL (ppm)	1000 ppm
Nunavut	OEL STEL (mg/m ³)	2576 mg/m ³
Nunavut	OEL STEL (ppm)	1000 ppm
Nunavut	OEL TWA (mg/m ³)	1901 mg/m ³
Nunavut	OEL TWA (ppm)	800 ppm
Northwest Territories	OEL STEL (mg/m ³)	2576 mg/m ³
Northwest Territories	OEL STEL (ppm)	1000 ppm
Northwest Territories	OEL TWA (mg/m ³)	1901 mg/m ³
Northwest Territories	OEL TWA (ppm)	800 ppm
Ontario	OEL TWA (ppm)	800 ppm
Prince Edward Island	OEL STEL (ppm)	1000 ppm
Québec	VEMP (mg/m ³)	1900 mg/m ³
Québec	VEMP (ppm)	800 ppm
Saskatchewan	OEL STEL (ppm)	1250 ppm
Saskatchewan	OEL TWA (ppm)	1000 ppm
Yukon	OEL STEL (mg/m ³)	1600 mg/m ³
Yukon	OEL STEL (ppm)	750 ppm
Yukon	OEL TWA (mg/m ³)	1400 mg/m ³
Yukon	OEL TWA (ppm)	600 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapours may be released. Ensure adequate ventilation, especially in confined areas. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid

Appearance : Aerosol, when allowed to accumulate is liquid. Viscous brown solution.

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor	: Hydrocarbon
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butylacetate=1)	: < 1
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: -44 - 410 °C (-47.2°F-770°F)
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: Not available
Solubility	: Insoluble in water.
Log Pow	: Not available
Log Kow	: Not available
Viscosity, Kinematic	: Not available
Viscosity, Dynamic	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Toxic gases.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not available.

Specific Target Organ Toxicity (Repeated Exposure): Not applicable.

Reproductive Toxicity: Not available.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Respiratory tract irritation. May cause drowsiness or dizziness. Asphyxia by lack of oxygen: risk of death.

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/Injuries After Skin Contact: May cause skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: May cause eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects. May be fatal if swallowed and enters airways.

Chronic Symptoms: Not classified.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Propane (74-98-6)	
LC50 Inhalation Rat (mg/l)	658 mg/l/4h
Butane (106-97-8)	
LC50 Inhalation Rat (mg/l)	30957 mg/m ³ (Exposure time: 4 h)
Calcium petroleum sulfonate (61789-86-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 4000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Not Classified

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Additional Information: Flammable vapors may accumulate in the container. Container under pressure. Do not drill or burn even after use. Empty product containers may contain hazardous residue. Do not reuse empty containers without commercial cleaning or reconditioning.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : AEROSOLS flammable

Identification Number : UN1950

Label Codes : 2.1

Marine Pollutant : Marine pollutant

ERG Number : 126



14.1.1 In Accordance with DOT – Limited Quantity by Ground

Proper Shipping Name : None

Hazard Class : None

Identification Number : None

Label Codes : None

ERG Number : 126



14.2 In Accordance with IMDG

Proper Shipping Name : AEROSOLS, flammable

Hazard Class : 2.1

Identification Number : UN1950

Label Codes : 2.1

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Marine pollutant : Marine pollutant

MFAG Number : 126



14.3 In Accordance with IATA

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name : Consult air regulations for most current rules

Identification Number :

Hazard Class :

Label Codes :

ERG Code (IATA) :

14.4 In Accordance with TDG

Proper Shipping Name : AEROSOLS, flammable

Hazard Class : 2.1

Identification Number : UN1950

Label Codes : 2.1

Marine Pollutant (TDG) : Marine pollutant



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

RCBS Press Storage Aerosol	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard

Propane (74-98-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Butane (106-97-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium petroleum sulfonate (61789-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Diethylene Glycol Monobutyl Ether (112-34-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Propane (74-98-6)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Butane (106-97-8)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Accidental Release Prevention Regulations - Sufficient Quantities
U.S. - Delaware - Accidental Release Prevention Regulations - Threshold Quantities
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - TCPA - Extraordinarily Hazardous Substances (EHS)
U.S. - Ohio - Accidental Release Prevention - Threshold Quantities
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term

Petroleum distillates, hydrotreated light (64742-47-8)

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual

U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Calcium petroleum sulfonate (61789-86-4)


U.S. - Texas - Effects Screening Levels - Long Term

U.S. - Texas - Effects Screening Levels - Short Term

Canadian Regulations

RCBS Press Storage Aerosol

WHMIS Classification	Class A - Compressed Gas Class B Division 5 - Flammable Aerosol Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---



Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
----------------------	--

Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas
----------------------	--

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

Petroleum distillates, hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Calcium petroleum sulfonate (61789-86-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification	Class B Division 3 - Combustible Liquid
----------------------	---

Diethylene Glycol Monobutyl Ether (112-34-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Listed on the Canadian Ingredient Disclosure List

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION

Revision date : 3/16/2015

RCBS Press Storage Aerosol

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 3	Flammable liquids Category 3
Liquefied gas	Gases under pressure Liquefied gas
Repr. 2	Reproductive toxicity Category 2
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
Skin Sens. 1B	Skin sensitization Category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Federal Cartridge Company
900 Ehlen Drive
Anoka, MN 55303
T 1-800-635-7656

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2